


Portable Air Conditioner Specifications	Ready
Chassis Size	Y1G
Product Image	
Hisense Model	AP-12CR1SGRS00
Customer Model Number	AP12CR1G
Volts	115
Frequency (Hz)	60
Amps (Cooling)	12.0
Watts (Cooling)	1410
L.R.A of compressor (A)	50.5
Fuse Size (Amps)	15
Power Cord Length - Cabinet to Wall	4ft.
Power Cord Color	Black
Power Plug Type (AMP/Plug)	LCDI(5-15P)
Height (in)	28 1/8
Height (mm)	714.0
Width (in)	17 3/8
Width (mm)	442.0
Depth (in)	12 4/8
Depth (mm)	318.0
Net Weight (lb)	70.5
Net Weight (kg)	32.0
Shipping Weight (lb)	77.7
Shipping Weight (kg)	35.0
Removable Filter	Yes
Washable PP filter	Yes
HEPA Filter	NO
Carton Height (in)	34 7/8
Carton Height (mm)	885
Carton Width (in)	19 5/8
Carton Width (mm)	498
Carton Depth (in)	15 2/8
Carton Depth (mm)	386
stack limit	3
Loading Capacity (40' HC Container)	425/284/134
Flexible Condenser Air Hose (Included)	Yes (1 - 5.9" Dia X 59"Length) (grey)
Window/Product Exhaust Adapters (2) - Included	Yes
Window Exhaust Adapter Rain Guard Cover (1) - included	NO
Additional Water tank	NO
Brand	RECHI
Compressor	44A2G1AG8#C

Portable Air Conditioner Specifications	Ready
<b>Chassis Size</b>	<b>Y1G</b>
<b>Product Image</b>	
Hisense Model	<b>AP-12CR1SGRS00</b>
Customer Model Number	<b>AP12CR1G</b>
Refrigerant type	R410A
Gas charge	16.93oz
BTU - Cool(SCC)	12,000
BTU - Heat(Watts)	NO
Cooling efficiency ration (CER):	8.6
Energy Star	No
Heating Rating Conditions	N/A
Design pressure high side (PSIG)	600
Design pressure low side (PSIG)	236
Cooling Rating Conditions	ASHRAE-128-2001
Sound (dBA High)	49
Sound (dBA Medium)	48
Sound (dBA Low)	47
Dehumidification - Pints/HR	2.81(at 35.0/28.3°C)
Approximate Square Foot Cooling	up to 400
Air Flow on High (CFM)	205
Air Flow on Medium (CFM)	180
Air Flow on Low (CFM)	160
Compressor Type	Rotary
Expansion Device	Capillary tube
Evaporator	Copper tube and blue aluminum fins (hydrophilic)
Condenser	Copper tube and aluminum fins (bare)
Unit Control type	Electronic
Fan Control	Button
Thermostat Control	Button
Display Type	LED
Sleep Mode	Yes(on the controller)
Dry Mode (auto speed only)	Yes
Water Full Indicator	Yes
Auto Cool (auto fan in cooling)	Yes(on the controller)
Smart Mode (remote access)	Yes(on the controller)
Rapid Cool(Jet) Mode (lowest temp & high speed) - Remote only	Yes(on the controller)
Fan Only	Yes - 3 Speed
Anion	NO
Cooling Speed Selections	3
Timer- (24 Hr On/Off)	Yes- (24 Hr on/off - 10 minutes Increments up to 24 Hrs)
Clock	on the remote controller
Air Swing (Motorized - Upward & Downward Motion)	Yes
Auto-Restart	Yes
Room Temperature Display Units (F or C) factory default	Yes
Fahrenheit to Celsius function	Yes
Vent System	Single Duct