




Minisplit Aurora MAS Series Indoor Unit

Model		MAS36H2AMV-X	
Power supply	Voltage type	208/230V,1Ph	
	Supply frequency	60Hz	
Min. Circuit ampacity	Min. Circuit ampacity	A 3.0	
 Fan motor	Model	ZKFP-58-8-1-5	
	Input	W 58.0	
	RLA (Certification)	A 0	
	Speed(Hi/Mi/Lo)	r/min 1200/950/750	
	Capacitor	μF /	
	Capacitor class	/	
	Insulation class	E	
	 Evaporator	Number of rows	2.0
Tube outside dia		mm Φ7	
Tube outside type		Inner groove tube	
Tube pitch(a)x row pitch(b)		mm 21x13.37	
Fin spacing		mm 1.2	
Fin type (code)		Hydrophilic aluminum	
Coil length x height x width		mm 965x189x26.74+965x84x26.74+945x147x26.74	
Number of circuits		5	
Dimension(W*D*H)		Body_Width(W)	mm 1259
		Body_Depth(D)	mm 282
	Body_Height(H)	mm 362	
Packing(W*D*H)	Packing_Width(W)	mm 1340	
	Packing_Depth(D)	mm 450	
	Packing_Height(H)	mm 385	
Net/Gross weight	Net weight	Kg 18.5	
	Gross weight	Kg 24.2	
Indoor side air flow(SH/Hi/Mi/Lo/Si)	Indoor side air flow(SH)	m3/h 1500	
	Indoor side air flow(Hi)	m3/h 1450	
	Indoor side air flow(Mi)	m3/h 1100	
	Indoor side air flow(Lo)	m3/h 800	
	Indoor side air flow(Si)	m3/h /	
Drainage water pipe dia	Drainage water pipe dia	/	
ESP	Rated	Pa /	
	Range	Pa /	
Throttle type	Throttle type	外机节流	
India specification	India rotor diameter	mm 0	
	India stepper motor model	0	
	India indoor control board insurance tube rated voltage	V 0	
	India indoor control board insurance tube rated current	A 0	
Loading quantity 20'GP/40'GP/40'HQ	Loading quantity_20'GP	set 130	
	Loading quantity_40'GP	set 264	
	Loading quantity_40'HQ	set 300	