

Project NO.				
Code			22020610000616	
Sale model			MAP12C1PSP	
Power supply		Ph-V-Hz	115V,1Ph	
Cooling	Capacity	Btu/hr	12000	
	Input	W	1350	
	Current	A	11.7	
	EER	W/W		2.60
		Btu/W.h		8.90
Moisture Removal (26.7/20.9℃)		L/h	1.67	
Moisture Removal (30/27.1℃)		L/h	0	
Moisture Removal (35/28.3℃)		L/h	2.38	
Starting current		A	50	
Compressor	Model		ASM106E4UCZD	
	Brand		GMCC	
	Capacity	W	3260	
	Input	W	1068	
	Rated current(RLA)	A	9.68	
	Locked rotor Amp(LRA)	A	55	
	Thermal protector		UP3-67	
	Thermal protector position		INTERNAL	
	Capacitor	uF	70.0	
	Refrigerant oil	ml	VG74/300	
Indoor side fan motor	Model		YKTS-90-4-14-1	
	Input	W	158.0	
	Capacitor	uF	15	
	Speed(hi/mi/lo)	r/min	1140/1070/970	
	Capacitor class		P0	
	Insulation class		B	
	Waterproofing class		/	
Evaporator	a.Number of rows		3.0	
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37	
	c.Fin spacing	mm	1.3	
	d.Fin type (code)		Hydrophilic aluminum	
	e.Tube outside dia.and type	mm	Φ7Inner groove tube	
	f.Coil length x height x width	mm	240x231x40.11	
	g.Number of circuits		2	
	Indoor side air flow (Hi/Mi/Lo)	m3/h	310/0/0	
	CFM	182.35///		
Indoor side noise level(Hi/Mi/Lo)	dB(A)	55.5/0/52.7		
Condenser	a.Number of rows		3.0	
	b.Tube pitch(a)x row pitch(b)	mm	14.5x12.56	
	c.Fin spacing	mm	1.2	
	d.Fin type (code)		Unhydrophilic aluminium	
	e.Tube outside dia.and type	mm	Φ5Inner groove tube	
	f.Coil length x height x width	mm	240x261x37.68	
	g.Number of circuits		2	
Outdoor side noise level (Hi)	dB(A)	61		
Refrigerant type	ozs	R410A		
Design pressure	MPa	///		
Plug type		LCDI(5-15P)		
Power cord type		14#x3		
Power cord length	mm	1900		
Power cord length	ft	6.23		
Control type		遙控式(Remote Control)		
Operation temp (room temp.)	℃		17-35	
	°F		/	
Application area (Cooling Standard)	m ²		16/23	
Application area (Cooling Standard)	sq.ft		172.22/247.57	
Application area (Cooling EPA)	sq.ft			
Application area (Cooling Standard) DOE	m ²		///	
Application area (Cooling Standard) DOE	sq.ft		///	
Dimension (W*D*H)	mm		355x345x703	
	in		13.98x13.58x27.68	
Packing (W*D*H)	mm		400x390x880	
	in		15.75x15.35x34.65	
Net/Gross weight	Kg		25.3/29.8	
	lb		55.78/65.70	
Loading quantity 20' /40' /40'HQ	Pieces		174/356/534	